TSW200

PoE+ GIGABIT ETHERNET SWITCH

SFP

2 x SFP ports for long-range Fiber-optic communication

MOUNTING

DIN rail and surface mounting options

PoE+

8 x PoE ports with 802.af, 802.3at standard support

DURABILITY

Rugged aluminium housing

POWER BUDGET

Total power budget at PSE up to 240 W

ETHERNET

8 x Gigabit Ethernet with speeds up to 1000 Mbps

TSW200

PRODUCT DESCRIPTION

// TSW200 is industrial unmanaged switch from Teltonika Networks.

// TSW200 is equipped with 2 SFP ports for long-range Fiber-optic communication and 8 Gigabit Ethernet ports which support IEEE802.af and IEE802.3at Power-over-Ethernet standards.

// Classified as power source equipment (PSE), it enables centralization of the power supply, providing up to 30 watts per port and reducing the effort for installing power. It has 10/100/1000 Mbps Ethernet ports to provide an economical high-bandwidth solution for your industrial Ethernet network.

// This rugged unmanaged industrial switch is ideal for professional high bandwidth applications where it is necessary to provide both: reliable data connection and power supply.

FRONT VIEW



BACK VIEW

Copyright © 2021, Teltonika Networks. Specifications and information given in this document are subject to change by Teltonika Networks without prior notice.

KEY FEATURES

HARDWARE

Power connector	2 pin, push-in, terminal block
Power consumption	Idle: < 2 W, Max: < 9 W (no PoE device connected)
PoE standard	802.3af/at (up to 30 W per port, total power budget - 240 W)
Ethernet	8 x 10/100/1000 Mbps Ethernet ports
SFP	2 x SFP port for Optical interface
Status LEDs	16 x Ethernet, 1 x Power, 2 x SFP activity
Ingress protection rating	IP30
Operating temperature	-40 °C to 75 °C
Housing	Aluminium housing with wall or DIN rail mounting option and grounding capability
Dimensions	132 x 44.2 x 95.1 mm
Weight	456 g
Installation	Desktop, wall or DIN Rail mountable (additional kit needed)

* PoE operates properly only when connected power supply outputs 44 V or higher voltage

PERFORMANCE SPECIFICATIONS

Bandwidth	Bandwidth 20 Gbps
Packet buffer	128 KB
Jumbo frame support	9216 bytes
MAC address table size	2K entries
Auto MDI/MDI-X Cable Detection	Yes

SOCIAL

@Teltonika Networks

@Teltonika Networks

@teltonikanetworksofficial

@Teltonika Networks

Copyright © 2021, Teltonika Networks. Specifications and information given in this document are subject to change by Teltonika Networks without prior notice.