



pro NEW



PSNpro

The helical precision planetary gearbox for low-noise operation and maximum performance

Thanks to its helical gearing, the **PSNpro** enables low-noise operation and maximum synchronisation quality. It is also ideal for high cycle torques. Its preloaded tapered roller bearings and square output flange ensure a high load capacity and allow high output shaft loads, even under extreme conditions.

Cyclic torque **14 - 1800 Nm**



Radial force **950 - 20000 N**



Axial force **2200 - 17000 N**



Torsional backlash **1 - 8 arcmin**



Protection class **IP65**




Frame sizes

- 55
- 70
- 90
- 115
- 142
- 190



2-stage



PSNpro



Precision Line



Helical gear



Preloaded tapered roller bearings




Extra long centering collar




Option: Reduced backlash




Option: Rack and pinion
Planetary gearbox (Details on page 158)



Coaxial gearbox



Equidirectional rotation



Square type output flange



Rotary shaft seal



Planet carrier in cage design



Option: Painted surface
– RAL 9005 Jet black

Detailed explanations of the technical features starting on page 201.

Code	Gearbox characteristics			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	p ⁽¹⁾
	Service life ⁽²⁾	L _h	h	20,000						
	Efficiency ⁽³⁾	η	%	97						1
				96						2
	Min. operating temperature	T _{min}	°C	-25 (-13)						
	Max. operating temperature	T _{max}	(°F)	90 (194)						
	Protection class			IP65						
S	Standard lubrication			Oil (lifetime lubrication)						
F	Food grade lubrication			Oil (lifetime lubrication)						
	Installation position			Any						
S	Standard backlash	φ	arcmin	< 6	< 3	< 3	< 3	< 3	< 3	1
				< 8	< 5	< 5	< 5	< 5	< 5	2
R	Reduced backlash	φ	arcmin	< 4	< 2	< 1	< 1	< 1	< 1	1
				< 6	< 3	< 1	< 1	< 1	< 1	2
	Torsional stiffness ⁽³⁾	C _{2t}	Nm / arcmin (lb _i .in/ arcmin)	1.3 - 1.9 (11 - 17)	3.6 - 5.0 (32 - 44)	10.5 - 13.9 (93 - 123)	28.0 - 39.0 (248 - 345)	62.0 - 88.0 (549 - 779)	181.0 - 246.0 (1602 - 2177)	1
				1.3 - 1.9 (11 - 17)	3.4 - 4.9 (30 - 43)	10.3 - 13.8 (91 - 122)	28.5 - 39.5 (252 - 350)	61.0 - 86.0 (540 - 761)	179.0 - 255.0 (1584 - 2257)	2
	Gearbox weight ⁽³⁾	m	kg (lb _m)	0.8 (1.7 - 1.9)	2.2 (4.8 - 4.9)	4.0 - 4.1 (8.8 - 8.9)	6.9 - 7.3 (15.3 - 16.1)	15.1 - 15.5 (33.3 - 34.2)	34.5 - 36.3 (76.1 - 80.1)	1
				1.1 (2.5)	2.2 (4.8 - 4.9)	4.1 - 4.2 (9.0 - 9.2)	8.2 - 8.4 (18.1 - 18.5)	16.3 - 16.8 (36.0 - 37.1)	37.5 - 39.4 (82.7 - 86.8)	2
S	Standard surface			Housing: Steel – heat-treated and post-oxidized (black)						
B	Painted surface ⁽⁴⁾			RAL 9005 Jet black						
	Running noise ⁽⁵⁾	L _{pA}	dB(A)	56	57	58	63	66	68	

Output shaft loads			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	p ⁽¹⁾
Maximum radial force	F _{r max}	N (lb _f)	950 (214)	3200 (719)	5500 (1236)	6000 (1349)	13000 (2923)	20000 (4496)	
Maximum axial force	F _{a max}		2200 (495)	3400 (764)	4500 (1012)	6500 (1461)	12000 (2698)	17000 (3822)	
Maximum tilting moment	M _{K max}	Nm (lb _f .in)	40 (353)	203 (1800)	419 (3709)	562 (4972)	1566 (13856)	2887 (25552)	

Input characteristics			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	p ⁽¹⁾
Clamping system diameter input (Code)	D26	mm	11 (C) ⁽⁵⁾	11 (C)	14 (D)	19 (E)	35 (G) ⁽⁵⁾	48 (K) ⁽⁵⁾	1
			14 (D)	14 (D) ⁽⁵⁾	19 (E) ⁽⁵⁾	24 (F) ⁽⁵⁾	42 (H)	-	
			-	19 (E)	24 (F)	35 (G)	-	-	
			11 (C) ⁽⁵⁾	11 (C) ⁽⁵⁾	11 (C)	14 (D)	19 (E)	35 (G) ⁽⁵⁾	2
			14 (D)	14 (D)	14 (D) ⁽⁵⁾	19 (E) ⁽⁵⁾	24 (F) ⁽⁵⁾	42 (H)	
-	-	19 (E)	24 (F)	35 (G)	-				
Mass moment of inertia input ⁽³⁾⁽⁵⁾	J _i	kgcm ² (lb _f .in.s ² 10 ⁻⁴)	0.096 - 0.126 (0.850 - 1.115)	0.150 - 0.294 (1.328 - 2.602)	0.439 - 0.920 (3.885 - 8.143)	1.147 - 2.775 (10.152 - 24.561)	6.475 - 13.112 (57.309 - 116.051)	21.695 - 53.182 (192.017 - 470.700)	1
			0.095 - 0.109 (0.841 - 0.965)	0.168 - 0.227 (1.487 - 2.009)	0.327 - 0.408 (2.894 - 3.611)	1.279 - 1.559 (11.320 - 13.798)	3.444 - 4.565 (30.482 - 40.404)	18.722 - 23.015 (165.704 - 203.700)	2
Average idle torque ⁽³⁾⁽⁵⁾	T ₀	Nm (lb _f .in)	0.15 - 0.30 (1 - 3)	0.30 - 0.75 (3 - 7)	0.60 - 1.45 (5 - 13)	1.00 - 3.00 (9 - 27)	2.30 - 7.95 (20 - 70)	5.20 - 17.65 (46 - 156)	1
			0.15 - 0.25 (1 - 2)	0.15 - 0.35 (1 - 3)	0.25 - 0.50 (2 - 4)	0.50 - 1.20 (4 - 11)	0.85 - 2.65 (8 - 23)	2.00 - 5.85 (18 - 52)	2
Max. bending moment based on the gearbox input flange	M _{b1}		10 (89)	18 (159)	38 (336)	80 (708)	180 (1593)	300 (2655)	1
			10 (89)	18 (159)	18 (159)	38 (336)	80 (708)	180 (1593)	2

(1) Number of stages

(2) Application specific configuration with NCP – www.neugart.com

(3) The ratio-dependent values can be retrieved in Tec Data Finder – www.neugart.com

(4) More information on page 183

(5) Reference clamping system diameter

Output torques			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	i ⁽¹⁾	p ⁽²⁾
Cyclic torque ⁽³⁾⁽⁴⁾	T _{2z}	Nm (lb _f .in)	20 (177)	48 (425)	114 (1009)	250 (2213)	520 (4602)	1110 (9824)	3	1
			25 (221)	68 (602)	150 (1328)	330 (2921)	700 (6196)	1480 (13099)	4	
			25 (221)	68 (602)	150 (1328)	330 (2921)	850 (7523)	1800 (15931)	5	
			18.5 (164)	45 (398)	108 (956)	300 (2655)	600 (5310)	1450 (12834)	7	
			18 (159)	40 (354)	84 (743)	190 (1682)	425 (3762)	-	8	
			13.5 (119)	32 (283)	72 (637)	190 (1682)	315 (2788)	850 (7523)	10	2
			20 (177)	48 (425)	114 (1009)	250 (2213)	650 (5753)	1500 (13276)	12	
			20 (177)	48 (425)	114 (1009)	250 (2213)	650 (5753)	1500 (13276)	15	
			25 (221)	68 (602)	150 (1328)	330 (2921)	850 (7523)	1800 (15931)	16	
			25 (221)	68 (602)	150 (1328)	330 (2921)	850 (7523)	1800 (15931)	20	
			25 (221)	68 (602)	150 (1328)	330 (2921)	850 (7523)	1800 (15931)	25	
			25 (221)	68 (602)	150 (1328)	330 (2921)	850 (7523)	1800 (15931)	35	
			25 (221)	68 (602)	150 (1328)	330 (2921)	850 (7523)	1800 (15931)	40	
			25 (221)	67 (593)	150 (1328)	330 (2921)	850 (7523)	1580 (13984)	50	
18.5 (164)	44 (389)	108 (956)	300 (2655)	600 (5310)	1450 (12834)	70				
13.5 (119)	32 (283)	72 (637)	190 (1682)	315 (2788)	850 (7523)	100				
Maximum torque ⁽³⁾⁽⁴⁾	T _{2max}	Nm (lb _f .in)	29 (257)	77 (682)	139 (1230)	300 (2655)	520 (4602)	1110 (9824)	3	1
			40 (354)	83 (735)	200 (1770)	400 (3540)	700 (6196)	1480 (13099)	4	
			40 (354)	79 (699)	184 (1629)	440 (3894)	870 (7700)	1850 (16374)	5	
			29 (257)	59 (522)	167 (1478)	395 (3496)	800 (7081)	1680 (14869)	7	
			28 (248)	64 (566)	134 (1186)	295 (2611)	490 (4337)	-	8	
			21 (186)	52 (460)	116 (1027)	280 (2478)	500 (4425)	1050 (9293)	10	2
			29 (257)	77 (682)	139 (1230)	395 (3496)	770 (6815)	1880 (16639)	12	
			29 (257)	77 (682)	139 (1230)	395 (3496)	770 (6815)	1880 (16639)	15	
			40 (354)	83 (735)	220 (1947)	520 (4602)	1030 (9116)	2210 (19560)	16	
			40 (354)	83 (735)	220 (1947)	520 (4602)	1030 (9116)	2210 (19560)	20	
			40 (354)	79 (699)	184 (1629)	440 (3894)	1070 (9470)	1960 (17347)	25	
			40 (354)	79 (699)	184 (1629)	440 (3894)	1070 (9470)	1960 (17347)	35	
			40 (354)	79 (699)	220 (1947)	520 (4602)	1170 (10355)	2210 (19560)	40	
			40 (354)	79 (699)	184 (1629)	440 (3894)	1070 (9470)	1960 (17347)	50	
29 (257)	51 (451)	167 (1478)	395 (3496)	800 (7081)	1680 (14869)	70				
21 (186)	52 (460)	116 (1027)	280 (2478)	500 (4425)	1050 (9293)	100				

PSNpro

⁽¹⁾ Ratios (i=n₁/n₂)
⁽²⁾ Number of stages
⁽³⁾ Application specific configuration with NCP – www.neugart.com
⁽⁴⁾ Based on reference clamping system diameter

Output torques			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	i ⁽¹⁾	p ⁽²⁾
Continuous torque ⁽³⁾	T _{2D}	Nm (lb _f .in)	11 (97)	30 (266)	62 (549)	155 (1372)	475 (4204)	1110 (9824)	3	1
			18.5 (164)	39 (345)	94 (832)	194 (1717)	600 (5310)	1380 (12214)	4	
			17.5 (155)	37 (327)	84 (743)	167 (1478)	550 (4868)	1230 (10886)	5	
			15.5 (137)	37 (327)	80 (708)	156 (1381)	500 (4425)	1070 (9470)	7	
			15 (133)	34 (301)	71 (628)	154 (1363)	425 (3762)	-	8	
			11 (97)	27 (239)	61 (540)	159 (1407)	315 (2788)	720 (6373)	10	
		17.5 (155)	40 (354)	77 (682)	200 (1770)	550 (4868)	1270 (11240)	12	2	
		17.5 (155)	41 (363)	79 (699)	200 (1770)	520 (4602)	1270 (11240)	15		
		25 (221)	55 (487)	80 (708)	194 (1717)	530 (4691)	1610 (14250)	16		
		25 (221)	57 (504)	87 (770)	194 (1717)	530 (4691)	1600 (14161)	20		
		25 (221)	57 (504)	76 (673)	164 (1452)	435 (3850)	1530 (13542)	25		
		25 (221)	61 (540)	89 (788)	190 (1682)	475 (4204)	1540 (13630)	35		
		25 (221)	61 (540)	94 (832)	200 (1770)	500 (4425)	0 (0)	40		
		25 (221)	57 (504)	103 (912)	220 (1947)	550 (4868)	1580 (13984)	50		
		15.5 (137)	40 (354)	92 (814)	220 (1947)	510 (4514)	1230 (10886)	70		
		11 (97)	27 (239)	61 (540)	162 (1434)	315 (2788)	720 (6373)	100		

Input speeds			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	i ⁽¹⁾	p ⁽²⁾
Continuous input speed ⁽³⁾⁽⁴⁾	n _{1D}	rpm	4050	2500	2050	1500	830	500	3	1
			4100	3150	1950	1650	1050	460	4	
			4950	3800	2500	2250	1500	650	5	
			5000	4500	3400	3200	2200	970	7	
			5000	4500	3350	3150	2600	-	8	
			5000	4500	4000	3500	2950	1400	10	
		3800	3800	3900	2500	1350	990	12	2	
		4300	4500	4500	3050	1950	1300	15		
		3650	4000	4300	3050	1850	1100	16		
		4100	4500	4500	3800	2300	1400	20		
		4250	4500	4500	4000	3050	1550	25		
		4850	4500	4500	4000	3500	2150	35		
		4900	4500	4500	4000	3500	2850	40		
		5000	4500	4500	4000	3500	2750	50		
		5000	4500	4500	4000	3500	3000	70		
		5000	4500	4500	4000	3500	3000	100		
Max. mechanical input speed ⁽³⁾	n _{1max}	rpm	10000	10000	10000	8500	6500	6000		1
			10000	10000	10000	10000	8500	6500		2

Output torques			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSNpro190	i ⁽¹⁾	p ⁽²⁾
Emergency stop torque ⁽⁴⁾⁽⁵⁾	T _{2Stop}	Nm (lb _f .in)	55 (487)	120 (1062)	210 (1859)	495 (4381)	1050 (9293)	2220 (19649)	3	1
			55 (487)	150 (1328)	280 (2478)	650 (5753)	1400 (12391)	2960 (26198)	4	
			55 (487)	150 (1328)	300 (2655)	650 (5753)	1750 (15489)	3600 (31863)	5	
			55 (487)	102 (903)	255 (2257)	650 (5753)	1390 (12303)	3240 (28676)	7	
			50 (443)	117 (1036)	295 (2611)	500 (4425)	850 (7523)	-	8	
			24 (212)	61 (540)	141 (1248)	345 (3054)	740 (6550)	1830 (16197)	10	
		55 (487)	150 (1328)	300 (2655)	650 (5753)	1340 (11860)	3260 (28853)	12	2	
		55 (487)	150 (1328)	300 (2655)	650 (5753)	1340 (11860)	3260 (28853)	15		
		55 (487)	150 (1328)	300 (2655)	650 (5753)	1780 (15754)	3600 (31863)	16		
		55 (487)	150 (1328)	300 (2655)	650 (5753)	1780 (15754)	3600 (31863)	20		
		55 (487)	150 (1328)	300 (2655)	650 (5753)	2000 (17701)	3600 (31863)	25		
		55 (487)	150 (1328)	300 (2655)	650 (5753)	2000 (17701)	3600 (31863)	35		
		55 (487)	150 (1328)	300 (2655)	650 (5753)	2000 (17701)	2970 (26287)	40		
		55 (487)	150 (1328)	300 (2655)	650 (5753)	1650 (14604)	3600 (31863)	50		
		55 (487)	89 (788)	255 (2257)	600 (5310)	1390 (12303)	3230 (28588)	70		
		24 (212)	61 (540)	116 (1027)	345 (3054)	740 (6550)	1830 (16197)	100		


⁽¹⁾ Ratios (i=n₁/n₂)

⁽²⁾ Number of stages

⁽³⁾ Application specific configuration with NCP – www.neugart.com

⁽⁴⁾ Based on reference clamping system diameter

⁽⁵⁾ Permitted 1000 times



Drawing corresponds to a PSNpro090 / 1-stage / smooth output shaft / 14 mm clamping system / motor adaptation – 2-part – round universal flange / B5 flange type motor

⁽¹⁾ The dimensions vary with the motor/gearbox flange. The input flange dimensions can be retrieved for each specific motor in Tec Data Finder at www.neugart.com

Geometry ⁽²⁾			PSNpro055	PSNpro070	PSNpro090	PSNpro115	PSNpro142	PSN1 pro90	p ⁽³⁾	Code
Pitch circle diameter output	D1		63 (2.480)	68 - 75 (2.677 - 2.953)	85 (3.346)	120 (4.724)	165 (6.496)	215 (8.465)		
Mounting bore output	D2	4x	5.5 (0.217)	5.5 (0.217)	6.5 (0.256)	9.0 (0.354)	11.0 (0.433)	13.5 (0.531)		
Shaft diameter output	D3	k6	12 (0.472)	16 (0.630)	22 (0.866)	32 (1.260)	40 (1.575)	55 (2.165)		
Shaft collar output	D4		16 (0.630)	21.5 (0.846)	31.5 (1.240)	41.5 (1.634)	57.5 (2.264)	76.5 (3.012)		
Centering diameter output	D5	g7	50 (1.969)	60 (2.362)	70 (2.756)	90 (3.543)	130 (5.118)	160 (6.299)		
Diagonal dimension output	D7		74 (2.913)	92 (3.622)	100 (3.937)	140 (5.512)	185 (7.283)	240 (9.449)		
Flange cross section output	Q1	■	55 (2.165)	70 (2.756)	80 (3.150)	110 (4.331)	142 (5.591)	190 (7.480)		
Min. total length	L1		103.5 (4.075)	134 (5.276)	157 (6.181)	202.5 (7.972)	261.5 (10.295)	310.5 (12.224)	1	
			127 (5.000)	162.5 (6.398)	179 (7.047)	224.5 (8.839)	292.5 (11.516)	355.5 (13.996)	2	
Housing length	L2		43 (1.693)	60.5 (2.382)	69.5 (2.736)	71 (2.795)	101.5 (3.996)	130.5 (5.138)	1	
			66.5 (2.618)	89 (3.504)	98 (3.858)	104.5 (4.114)	139 (5.472)	194 (7.638)	2	
Centering depth output	L7		12 (0.472)	19 (0.748)	17.5 (0.689)	28 (1.102)	28 (1.102)	28 (1.102)		
Flange thickness output	L8		6 (0.236)	7 (0.276)	8 (0.315)	10 (0.394)	12 (0.472)	15 (0.591)		
Center hole (DIN 332. type DR)	C		M4x10	M5x12.5	M8x19	M12x28	M16x36	M20x42		
Motor shaft diameter j6/k6	D20		More information on page 191/192							
Clamping system diameter input	D26		More information on page 94							
Output shaft with feather key (DIN 6885-1)			A 4x4x18	A 5x5x25	A 6x6x28	A 10x8x50	A 12x8x65	A 16x10x70		
Feather key width (DIN 6885-1)	B1		4 (0.157)	5 (0.197)	6 (0.236)	10 (0.394)	12 (0.472)	16 (0.630)		A
Shaft height including feather key (DIN 6885-1)	H1		13.5 (0.531)	18 (0.709)	24.5 (0.965)	35 (1.378)	43 (1.693)	59 (2.323)		
Shaft length output	L3		36 (1.417)	48 (1.890)	56 (2.205)	88 (3.465)	110 (4.331)	112 (4.409)		
Shaft length from shoulder	L4		23 (0.906)	28 (1.102)	36 (1.417)	58 (2.283)	80 (3.150)	82 (3.228)		
Feather key length	L5		18 (0.709)	25 (0.984)	28 (1.102)	50 (1.969)	65 (2.559)	70 (2.756)		
Distance from shaft end	L6		2 (0.079)	2 (0.079)	4 (0.157)	4 (0.157)	8 (0.315)	6 (0.236)		
Smooth output shaft										
Shaft length output	L3		36 (1.417)	48 (1.890)	56 (2.205)	88 (3.465)	110 (4.331)	112 (4.409)		B
Shaft length from shoulder	L4		23 (0.906)	28 (1.102)	36 (1.417)	58 (2.283)	80 (3.150)	82 (3.228)		
Splined output shaft (DIN 5480)			-	W16x 0.8x18x6m	W22x 1.25x16x6m	W32x 1.25x24x6m	W40x 2.0x18x6m	W55x 2.0x26x6m		C
Width of gearing	L _v		-	15 (0.591)	15 (0.591)	15 (0.591)	20 (0.787)	22 (0.866)		
Shaft length output	L3		-	46 (1.811)	46 (1.811)	56 (2.205)	70 (2.756)	71.5 (2.815)		
Shaft length from shoulder	L4		-	26 (1.024)	26 (1.024)	26 (1.024)	40 (1.575)	41.5 (1.634)		

⁽²⁾ Dimensions in mm

⁽³⁾ Number of stages